

## 8x8/7x9 阵列 LED 驱动器

### 8x8/7x9 MATRIX LED DRIVER

#### ■ FEATURES

- Supply voltage range: 2.5V to 5.5V
- 8 current sinks
- Support 8×n (n=1~8), 7×9 LED matrix configurations
- Individual 256 PWM control steps
- 256 DC current steps for each CSx
- 64 global current steps
- SDB rising edge reset I<sup>2</sup>C module
- 32kHz PWM frequency (0.25k~80kHz programmable)
- 1MHz I<sup>2</sup>C-compatible interface
- Individual open and short error detect function
- PWM 180 degree phase shift
- Spread Spectrum
- De-Ghost
- SOP24 package
- 输入电压范围: 2.5V-5.5V
- 8路电流源
- 支持8×n (n=1~8), 7×9 LED 阵列配置
- 独立的256阶PWM控制台阶
- 每个CSx有256个直流台阶
- 64个整体电流台阶
- SDB上升沿复位I<sup>2</sup>C模块
- 32kHz的PWM频率 (0.25k~80kHz可编程)
- 支持1MHz的I<sup>2</sup>C接口
- 独立的开路 and 短路错误检测功能
- PWM信号180度相位转变功能
- 扩频功能
- De-Ghost
- SOP24 封装

#### ■ APPLICATIONS

- White goods LED display panel
- IOT device
- 白色家电LED面板显示
- IOT设备

#### ■ DESCRIPTION

LED Matrix programmed via 1MHz I<sup>2</sup>C compatible interface. Each LED can be dimmed individually with 8-bit PWM data, and each CSx has 8-bit DC scaling (Color Calibration) data which allowing 256 steps of linear PWM dimming for each dot and 256 steps of DC current adjustable level for each CSx.

Additionally, each LED open and short state can be detected, HTR3239 store the open or short information in Open-Short Registers. The Open-Short Registers allowing MCU to read out via I<sup>2</sup>C compatible interface. Inform MCU whether there are LEDs open or short and the locations of open or short LEDs.


The HTR3239 operates from 2.5V to 5.5V and features a very low shutdown and operational current. HTR3239 is available in SOP24 package. It operates from 2.5V to 5.5V over the temperature range of -40°C to +125°C.

HTR3239是一款通过1MHz的I<sup>2</sup>C接口进行编程的支持8×8或7×9阵列的LED驱动芯片, 每路LED都支持8位PWM数据进行独立调光, 并且每路CSx都有8位的直流扫描数据用来支持每个点的256阶的线性PWM调光, 并且每个CSx都支持256阶的直流电流可调节等级。

另外, 每个LED的开路和短路状态都能被检测, HTR3239能够把开路和短路信息存储在Open-Short寄存器组中。这个寄存器组允许MCU通过I<sup>2</sup>C接口读取用以告诉MCU这些LED灯是否是在开路或者短路状态以及位置信息。

HTR3239的工作电压在2.5V到5.5V之间, 并且关断电流和工作电流都非常小。HTR3239支持SOP24封装, 可在2.5V到5.5V和-40°C to +125°C下工作。

## ■ TYPICAL APPLICATION




Driving 8×8 LEDs

The VDD should be smaller than VCC. And if VDD is lower than 3.0V, it is recommended to add a level shift circuit to avoid extra shutdown current.


These Ro resistors are for offloading the thermal dissipation ( $P=I^2R$ ) away from the HTR3239, for mono red/yellow/orange LED, if VCC = 3.3V, Ro resistors are not needed.

VDD应小于VCC。如果VDD小于3.0V，建议增加使用电平转换电路，以避免额外的关断电流。

Ro电阻是为了减少HTR3239的热耗散。若VCC=3.3V，驱动的是单色灯（红/黄/橙），可不接Ro电阻。



Driving 7×9 LEDs





## Driving 18 RGBs

These Ro resistors are for offloading the thermal dissipation ( $P=I^2R$ ) away from the HTR3239, for red LED, it is recommended to use about 30Ohm more than blue/green LED, to offload more extra voltage due to lower forward voltage of red LED.


Ro电阻是为了减少HTR3239的热耗散。红灯的Ro电阻建议使用510hm，比蓝灯/绿灯的Ro电阻大约30 Ohm。

**ORDERING INFORMATION**

| Part Number | Package Type | Marking                         | Operating Temperature Range | Shipping Package / MOQ     |
|-------------|--------------|---------------------------------|-----------------------------|----------------------------|
| HTR3239SPNR | SOP24 (SPN)  | HTR3239<br>YYYMAAB <sup>1</sup> | -40℃~125℃                   | Tape and Reel (R) /<br>TBD |

**Part Number**

**Production Tracking Code**


## ■ TERMINAL CONFIGURATION



Top View

## ■ TERMINAL FUNCTION

| Terminal No. | Name    | Description                                              |
|--------------|---------|----------------------------------------------------------|
| 10~14, 16~17 | CS1~CS7 | Current sinks output. 电流源输出                              |
| 4,15         | GND     | Ground. 地                                                |
| 18           | SW9/CS8 | Switch power source / current sinks output. 开关电源/电流源输出   |
| 19~24, 1~2   | SW8~SW1 | Switch power source 开关电源                                 |
| 3            | VCC     | Power supply. 电源输入端                                      |
| 5            | ISET    | Current setting pin. 电流设置引脚                              |
| 6            | SDA     | I <sup>2</sup> C serial data. I <sup>2</sup> C时钟         |
| 7            | SCL     | I <sup>2</sup> C serial clock. I <sup>2</sup> C数据        |
| 8            | SDB     | Shutdown the chip when pull to low. 当拉低时关闭芯片             |
| 9            | AD      | I <sup>2</sup> C Address setting. I <sup>2</sup> C的地址设置端 |

## ■ SPECIFICATIONS<sup>1</sup>

### ● Absolute Maximum Ratings<sup>2</sup>

| PARAMETER                                                                                           | Symbol           | MIN  | TYP  | MAX     | UNIT |
|-----------------------------------------------------------------------------------------------------|------------------|------|------|---------|------|
| Power supply voltage for VCC                                                                        | VCC              | -0.3 |      | 6       | V    |
| Voltage at SCL, SDA, SDB, SWx, CSx                                                                  | V <sub>I</sub>   | -0.3 |      | VCC+0.3 | V    |
| Moisture Sensitivity Level (MSL)                                                                    |                  |      | MSL3 |         |      |
| Ambient Operating Temperature                                                                       | T <sub>A</sub>   | -40  |      | 125     | °C   |
| Junction Temperature                                                                                | T <sub>J</sub>   | -40  |      | 125     | °C   |
| Storage Temperature                                                                                 | T <sub>STG</sub> | -65  |      | 150     | °C   |
| Package thermal resistance, junction to ambient (4 layer standard test PCB based on JEDEC standard) | θ <sub>JA</sub>  |      | 40   |         | °C/W |
| ESD (HBM)                                                                                           |                  |      | ±8   |         | kV   |
| ESD (CDM)                                                                                           |                  |      | ±1   |         | kV   |

### ● Main Electrical Characteristics

Condition: T<sub>A</sub> = 25°C, VCC = 3.6V, unless otherwise specified

| PARAMETER                                                                                     | Symbol              | CONDITION                                                                    | MIN | TYP  | MAX | UNIT |
|-----------------------------------------------------------------------------------------------|---------------------|------------------------------------------------------------------------------|-----|------|-----|------|
| Power supply voltage for VCC                                                                  | VCC                 |                                                                              | 2.5 |      | 5.5 | V    |
| Quiescent power supply current                                                                | I <sub>CC</sub>     | V <sub>SDB</sub> = VCC, all LEDs off                                         |     | 2    | 3   | mA   |
| Shutdown current                                                                              | I <sub>SD</sub>     | V <sub>SDB</sub> = 0V                                                        |     | 3    | 5   | uA   |
|                                                                                               |                     | V <sub>SDB</sub> = VCC, Configuration Register written "0000 0000"           |     | 3    | 5   | uA   |
| Maximum constant current of CSx                                                               | I <sub>OUT</sub>    | R <sub>ISET</sub> =10kΩ, GCC= "100 0000", SL=0xFF                            |     | 35   |     | mA   |
| Average current on each LED<br>I <sub>LED</sub> = I <sub>OUT(PEAK)</sub> /Duty                | I <sub>LED</sub>    | R <sub>ISET</sub> =10kΩ, GCC= "100 0000", SL=0xFF, n=8, Duty=1/8.29          |     | 4.22 |     | mA   |
| Current switch headroom voltage SWx                                                           | V <sub>HR</sub>     | I <sub>SWITCH</sub> =600mA R <sub>ISET</sub> =10kΩ, GCC= "100 0000", SL=0xFF |     | 500  |     | mV   |
| Current sink headroom voltage CSx                                                             |                     | I <sub>SINK</sub> =34mA, R <sub>ISET</sub> =10kΩ, GCC= "100 0000", SL=0xFF   |     | 400  |     | mV   |
| Period of scanning                                                                            | t <sub>SCAN</sub>   |                                                                              |     | 30   |     | us   |
| Non-overlap blanking time during scan, the SWx and CSy are all off during this time           | t <sub>NOL1</sub>   |                                                                              |     | 0.8  |     | us   |
| Delay total time for CS1 to CS8, during this time, the SWx is on but CSx is not all turned on | t <sub>NOL2</sub>   |                                                                              |     | 0.27 |     | us   |
| Thermal shutdown                                                                              | T <sub>SD</sub>     |                                                                              |     | 160  |     | °C   |
| Thermal shutdown hysteresis                                                                   | T <sub>SD_HYS</sub> |                                                                              |     | 20   |     | °C   |
| Output voltage of ISET pin                                                                    | VISET               |                                                                              |     | 1    |     | V    |

### ● Logic Electrical Characteristics (SDA, SCL, AD, SDB)

| PARAMETER                        | Symbol           | CONDITION                                 | MIN | TYP | MAX             | UNIT |
|----------------------------------|------------------|-------------------------------------------|-----|-----|-----------------|------|
| Logic "0" input voltage          | V <sub>IL</sub>  | V <sub>CC</sub> = 2.5V~5.5V, LGC= "0"     | GND |     | 0.4             | V    |
| Logic "1" input voltage          | V <sub>IH</sub>  | V <sub>CC</sub> = 2.5V~5.5V, LGC= "0"     | 1.4 |     | V <sub>CC</sub> | V    |
| Logic "0" input voltage          | V <sub>IL</sub>  | V <sub>CC</sub> = 2.5V~5.5V, LGC= "1"     | GND |     | 0.6             | V    |
| Logic "1" input voltage          | V <sub>IH</sub>  | V <sub>CC</sub> = 2.5V~5.5V, LGC= "1"     | 2.4 |     | V <sub>CC</sub> | V    |
| Input schmitt trigger hysteresis | V <sub>HYS</sub> | V <sub>CC</sub> =3.6V, LGC= "0", LGC= "1" |     | 0.2 |                 | V    |
| Logic "0" input current          | I <sub>IL</sub>  | SDB=L, V <sub>INPUT</sub> = L             |     | 5   |                 | nA   |


<sup>1</sup> Depending on parts and PCB layout, characteristics may be changed.

<sup>2</sup> Stresses beyond those listed under absolute maximum ratings may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under recommended operating conditions is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

|                         |          |                      |  |   |  |    |
|-------------------------|----------|----------------------|--|---|--|----|
| Logic "1" input current | $I_{IH}$ | SDB=L, $V_{INPUT}=H$ |  | 5 |  | nA |
|-------------------------|----------|----------------------|--|---|--|----|

● **I<sup>2</sup>C Control Port**

| PARAMETER                                                                                    | Symbol        | MIN | TYP | MAX | MIN  | TYP | MAX  | UNIT |
|----------------------------------------------------------------------------------------------|---------------|-----|-----|-----|------|-----|------|------|
| Serial-Clock frequency                                                                       | $f_{SCL}$     |     |     | 400 |      |     | 1000 | kHz  |
| Bus free time between a STOP and a START condition                                           | $t_{BUF}$     | 1.3 |     |     | 0.5  |     |      | us   |
| Hold time (repeated) START condition. After this period, the first clock pulse is generated. | $t_{H(STA)}$  | 0.6 |     |     | 0.26 |     |      | us   |
| Setup time for a repeated START condition                                                    | $t_{SU(STA)}$ | 0.6 |     |     | 0.26 |     |      | us   |
| Setup Time for SCL to STOP condition                                                         | $t_{SU(STO)}$ | 0.6 |     |     | 0.26 |     |      | us   |
| Data hold time                                                                               | $t_{H(DAT)}$  |     |     |     |      |     |      | us   |
| Setup Time, SDA to SCL                                                                       | $t_{SU(DAT)}$ | 100 |     |     | 60   |     |      | ns   |
| Required Pulse Duration, SCL HIGH                                                            | $t_{HIGH}$    | 0.7 |     |     | 0.26 |     |      | us   |
| Required Pulse Duration, SCL LOW                                                             | $t_{LOW}$     | 1.3 |     |     | 0.5  |     |      | us   |
| Rise Time, SCL and SDA                                                                       | $T_r$         |     |     | 300 |      |     | 120  | ns   |
| Fall Time, SCL and SDA                                                                       | $T_f$         |     |     | 300 |      |     | 120  | ns   |



## APPLICATION INFORMATION

### 1 Power Supplies

The HTR3239 uses a serial bus, which conforms to the I<sup>2</sup>C protocol, to control the chip's functions with two wires: SCL and SDA. The chip has a 7-bit slave address (A7:A1), followed by the R/W bit, A0.

The HTR3239 supports 1MHz write and read operations. The value of bits A1 and A2 are decided by the connection of the AD pin.

The complete slave address is:

HTR3239 使用两条符合 I<sup>2</sup>C 通信协议的串行传输线 SDA 和 SCL 来控制芯片的工作方式。HTR3239 使用 7 位的从地址 (A7:A1)，最后一位为读写位

HTR3239 支持 1MHz 的读写操作，A1 和 A2 位由 AD 引脚的连接来决定。

完整的地址为：

Table1 Slave Address (Write only)

| Bit   | A7:A3 | A2:A1 | A0  |
|-------|-------|-------|-----|
| Value | 01101 | AD    | 0/1 |

AD connected to GND, AD = 00; AD connected to VCC, AD = 11; AD connected to SCL, AD = 01; AD connected to SDA, AD = 10;

The SCL line is uni-directional. The SDA line is bi-directional (open-collector) with a pull-up resistor (typically 400K IIC with 4.7k $\Omega$ , 1MHz IIC with 1k $\Omega$ ). The maximum clock frequency specified by the I<sup>2</sup>C standard is 1MHz. In this discussion, the master is the microcontroller and the slave is the HTR3239.

The SDA is latched in on the stable high level of the SCL. When there is no interface activity, the SDA line should be held high.

The "START" signal is generated by lowering the SDA signal while the SCL signal is high. The start signal will alert all devices attached to the I<sup>2</sup>C bus to check the incoming address against their own chip address.

The 8-bit chip address is sent next, most significant bit first. Each address bit must be stable while the SCL level is high.

After the last bit of the chip address is sent, the master checks for the HTR3239's acknowledge. The master releases the SDA line high (through a pull-up resistor). Then the master sends an SCL pulse. If the HTR3239 has received the address correctly, then it holds the SDA line low during the SCL pulse. If the SDA line is not low, then the master should send a "STOP" signal (discussed later) and abort the transfer.

Following acknowledge of HTR3239, the register address byte is sent, most significant bit first. HTR3239 must generate another acknowledge indicating that the register address has been received.

Then 8-bit of data byte are sent next, most significant bit first. Each data bit should be valid while the SCL level is stable high. After the data byte is sent, the HTR3239 must generate another acknowledge to indicate that the data was received.

The "STOP" signal ends the transfer. To signal "STOP", the SDA signal goes high while the SCL signal is high..

AD 连接至 GND, AD = 00; AD 连接至 VCC, AD = 11; AD 连接至 SCL, AD = 01; AD 连接至 SDA, AD = 10;

I<sup>2</sup>C 总线支持数据双向传输。SCL 为单向端口；SDA 为双向端口，开漏输出驱动，需外接上拉电阻(典型值为 400k 下为 4.7k, 1M 下为 1k)。最大时钟频率为 1MHz。在这种情况下，主控制器为单片机等控制器，从器件为 HTR3239。

在 SCL 为稳定的高电平时，SDA 为闭锁状态，并且在不使用的时候应保持高电平。

“开始”信号由 SCL 为高电平时将 SDA 拉低产生。“开始”信号会提醒所有的设备接收 I<sup>2</sup>C 总线上即将到来的地址与自己的地址进行比较。

接着发送的是 8bit 芯片地址，高位优先。在 SCL 为高电平的时候每个地址位必须保持稳定。

在最后一位传送出去后，主控制器应检测 HTR3239 的应答信号。主控制器通过上拉电阻释放 SDA 为高电平，然后使 SCL 发送一个脉冲。如果 HTR3239 正确的接收到 8 位数据，在 SCL 的脉冲期间它将使 SDA 拉低；如果 SDA 线不为低，则表示数据没有正确接收，主控制器将会发送一个“停止”信号并且中断数据传递。

在 HTR3239 的应答信号发送之后，寄存器的地址将被发送，高位优先。寄存器地址发出后，HTR3239 必须再产生一个应答位来表示寄存器地址已被正确接收。

接下来传送的是 8 位的寄存器数据。在 SCL 保持稳定的高电平时每位数据都是有效的。8 位数据传送完后，HTR3239 同样需要产生一个应答位来表示数据的正确接收。

传送结束后需要发送“停止”信号。结束信号由 SCL 为高时将 SDA 拉高。




Figure 1 I²C Interface Timing




Figure 2 Bit Transfer

### ADDRESS AUTO INCREMENT

To write multiple bytes of data into HTR3239, load the address of the data register that the first data byte is intended for. During the HTR3239 acknowledge of receiving the data byte, the internal address pointer will increment by one. The next data byte sent to HTR3239 will be placed in the new address, and so on. The auto increment of the address will continue as long as data continues to be written to HTR3239 (Figure 4).

如果有多个数据要传送给 HTR3239，只需求发送第一个数据写入的寄存器地址。在 HTR3239 接收数据器件，寄存器地址会自动加 1，下一个传送的数据将写入新的寄存器地址中，如此继续，直到 I²C 写入“停止”信号。如下图 4。




Figure 3 Typical I²C Writing




Figure 4 I²C Writing with Automatic Address Increment

## READ OPERATION

Most of the registers can be read.

To read the register, after I<sup>2</sup>C start condition, the bus master must send the HTR3239 device address with the R/W bit set to “0”, followed by the register address which determines which register is accessed. Then restart I<sup>2</sup>C, the bus master should send the HTR3239 device address with the R/W bit set to “1”. Data from the register defined by the command byte is then sent from the HTR3239 to the master. (Figure 5)

大部分的寄存器都是可读的。

要读取寄存器的话，在 I<sup>2</sup>C 启动信号以后，主机在发送 HTR3239 的器件地址时 R/W 位给 0，然后发送寄存器地址决定哪个寄存器被选中，然后发送 I<sup>2</sup>C 重启信号，之后主机在发送 HTR3239 的器件地址时 R/W 位给 1，之后倍选中的寄存器中的数据就会由 HTR3239 发送到主机(如图 5)。




Figure 5 I<sup>2</sup>C Reading

## 2 SCANNING TIMING




Figure 6 Scanning Timing

As shown in Figure above, the SW1~SW9 is turned on by serial, LED is driven 15 by 9 within the SWx (x=1~9) on time (SWx, x=1~9 is source and it is high when LED on), including the non-overlap blanking time during scan, the duty cycle of SWx (active high, x=1~9) is(n=9):

$$Duty = \frac{30us}{30us + 0.8us + 0.27us} \times \frac{1}{9}$$

Or (n=8):

$$Duty = \frac{30us}{30us + 0.8us + 0.27us} \times \frac{1}{8}$$

Where 30μs is t<sub>SCAN</sub>, the period of scanning and 0.8μs is t<sub>NOL1</sub>, the non-overlap time and 0.27μs is the CSx delay time.

### 3 PWM CONTROL

After setting the I<sub>OUT</sub> and GCC, the brightness of each LEDs (LED average current (ILED)) can be modulated with 256 steps by PWM Register, as described in following Formula.

$$I_{LED} = \frac{PWM}{256} \times I_{OUT(PEAK)} \times Duty$$

Writing new data continuously to the registers can modulate the brightness of the LEDs to achieve a breathing effect.

### 4 Gamma Correction

In order to perform a better visual LED breathing effect we recommend using a gamma corrected PWM value to set the LED intensity. This results in a reduced number of steps for the LED intensity setting, but causes the change in intensity to appear more linear to the human eye.

Gamma correction, also known as gamma compression or encoding, is used to encode linear luminance to match the non-linear characteristics of display. Since the HTR3239 can modulate the brightness of the LEDs with 256 steps, a gamma correction function can be applied when computing each subsequent LED intensity setting such that the changes in brightness matches the human eye's brightness curve.

Choosing more gamma steps provides for a more continuous looking breathing effect. This is useful for long reathing cycles. The recommended configuration is defined by the breath cycle T. When T=1s, choose 32 gamma steps, when T=2s, choose 64 gamma steps. The user must decide the final number of gamma steps not only by the LED itself, but also based on the visual performance of the finished product.

如上图所示, SW1~SW9 依次打开, 15×9 个 LED 随着 SWx 依次打开 (SW 是电源, 当它为高时 LED 打开), 在扫描时包含了不相交空余时间, SWx 的占空比 (高有效, x=1~9):

$$Duty = \frac{30us}{30us+0.8us+0.27us} \times \frac{1}{9} (n=9)$$

$$Duty = \frac{30us}{30us+0.8us+0.27us} \times \frac{1}{8} (n=8)$$

30us 是 t<sub>SCAN</sub>, 是扫描周期, 0.8us 是 t<sub>NOL1</sub>, 确保不相交的时间, 0.27us 是各路 CSx 的之间的延时。

在设置好 I<sub>OUT</sub> 和 GCC 之后, 每个 LED 灯的亮度都可以通过 PWM 寄存器进行 256 级调节, 公式如下:

$$I_{LED} = \frac{PWM}{256} \times I_{OUT(PEAK)} \times Duty$$

连续不断地对寄存器写入新的数据就可以调节灯的亮度, 从而实现呼吸效果。

使用 HTR3239 实现 LED 呼吸效果时, 为得到更好的呼吸效果, 建议对呼吸控制进行非线性修正。

HTR3239 内部实现线性的 256 级 PWM 调光。由于人视觉对亮度的误差, 电流线性增加时, 视觉上会感觉到呼吸开始时亮度变化快, 然后很快进入亮度饱和的问题。为了解决这个问题, 在呼吸时, 引入伽马补偿的方法, 达到视觉效果的线性。

为了显示更细腻的效果, 可采取更多级的输出, 防止呼吸时产生可观察到的亮度跳变。推荐的经验值是, 从最暗到最亮的呼吸周期 T 内, 当 T=1s, 推荐伽马补偿 32 级; 当 T=2s, 推荐伽马补偿 64 级, 以此类推。此推荐是 LED 没有任何遮挡下的经验值。若 LED 有挡光板, 可采用更少的亮度登记实现。具体等级数, 可根据实际测试调节。

Table2 32 Gamma Steps With 256 PWM Steps

|       |       |       |       |       |       |       |       |
|-------|-------|-------|-------|-------|-------|-------|-------|
| C(0)  | C(1)  | C(2)  | C(3)  | C(4)  | C(5)  | C(6)  | C(7)  |
| 0     | 1     | 2     | 4     | 6     | 10    | 13    | 18    |
| C(8)  | C(9)  | C(10) | C(11) | C(12) | C(13) | C(14) | C(15) |
| 22    | 28    | 33    | 39    | 46    | 53    | 61    | 69    |
| C(16) | C(17) | C(18) | C(19) | C(20) | C(21) | C(22) | C(23) |
| 78    | 86    | 96    | 106   | 116   | 126   | 138   | 149   |
| C(24) | C(25) | C(26) | C(27) | C(28) | C(29) | C(30) | C(31) |
| 161   | 173   | 186   | 199   | 212   | 226   | 240   | 255   |




Figure 7 Gamma Correction (32 Steps)

Table3 64 Gamma Steps With 256 PWM Steps

| C(0)  | C(1)  | C(2)  | C(3)  | C(4)  | C(5)  | C(6)  | C(7)  |
|-------|-------|-------|-------|-------|-------|-------|-------|
| 0     | 1     | 2     | 3     | 4     | 5     | 6     | 7     |
| C(8)  | C(9)  | C(10) | C(11) | C(12) | C(13) | C(14) | C(15) |
| 8     | 10    | 12    | 14    | 16    | 18    | 20    | 22    |
| C(16) | C(17) | C(18) | C(19) | C(20) | C(21) | C(22) | C(23) |
| 24    | 26    | 29    | 32    | 35    | 38    | 41    | 44    |
| C(24) | C(25) | C(26) | C(27) | C(28) | C(29) | C(30) | C(31) |
| 47    | 50    | 53    | 57    | 61    | 65    | 69    | 73    |
| C(32) | C(33) | C(34) | C(35) | C(36) | C(37) | C(38) | C(39) |
| 77    | 81    | 85    | 89    | 94    | 99    | 104   | 109   |
| C(40) | C(41) | C(42) | C(43) | C(44) | C(45) | C(46) | C(47) |
| 114   | 119   | 124   | 129   | 134   | 140   | 146   | 152   |
| C(48) | C(49) | C(50) | C(51) | C(52) | C(53) | C(54) | C(55) |
| 158   | 164   | 170   | 176   | 182   | 188   | 195   | 202   |
| C(56) | C(57) | C(58) | C(59) | C(60) | C(61) | C(62) | C(63) |
| 209   | 216   | 233   | 230   | 237   | 244   | 251   | 255   |




Figure 8 Gamma Correction (64 Steps)

## 5 OPEN/SHORT DETECT FUNCTION

HTR3239 has open and short detect bit for each LED.

Before using the open/short detect function, the following settings should be followed:

- (1) The SSD of reg 0xA0 should be enabled;
- (2) GCC (reg 0xA1) should be not “0x00”;
- (3) LSB of SL (reg 0x92 ~ 0x9F) should be “1”;
- (4) PWM (reg 0x03~ 0x8F) should be not “0x00”;
- (5) Write reg 0xB0 as 0x00, so that neither pullup nor pulldown resistor exists for SWx.

After that, by setting the OSDE bits of the Configuration Register (A0h) from “00” to “01” or “10”, the LED Open/short Register will start to store the open/short information and after at least 2 scanning cycles and the MCU can get the open/short information by reading the B3h~C4h, the open/short data will not get refreshed when setting the OSDE bit of the Configuration Register.

The detect action is one-off event and each time before reading out the open/short information, the OSDE bit of the Configuration Register (A0h) need to be set from “0” to “1” (clear before set operation).

## 6 DE-GHOST FUNCTION

The “ghost” term is used to describe the behavior of an LED that should be OFF but instead glows dimly when another LED is turned ON. A ghosting effect typically can occur when multiplexing LEDs. In matrix architecture any parasitic capacitance found in the constant-current outputs or the PCB traces to the LEDs may provide sufficient current to dimly light an LED to create a ghosting effect.

To prevent this LED ghost effect, the HTR3239 has integrated Pull down resistors for each SWx (x=1~9) and Pull up resistors for each CSy (y=1~16). Select the right SWx Pull down resistor (B0h) and CSy Pull up resistor (B0h) which eliminates the ghost LED for a particular matrix layout configuration.

## 7 SHUTDOWN MODE

Shutdown mode can be used as a means of reducing power consumption. During shutdown mode all registers retain their data.

### Software Shutdown

By setting SSD bit of the Configuration Register (A0h) to “0”, the HTR3239 will operate in software shutdown mode. When the HTR3239 is in software shutdown, all current sources are switched off, so that the matrix is blanked. All registers can be operated.

HTR3239 每个 LED 都有一个开路 and 短路检测位。

在使用开短路检测功能前需要设置：

- (1) 0xA0 中的 SSD 需使能；
- (2) 0xA1 的全局电流设置为非 0；
- (3) 0x92~0x9F 的 SL 最低位为 1；
- (4) 0x03~0x8F 的 PWM 设置为非 0；
- (5) 0xB0 写 0，不要有上拉下拉。

随后通过设置配置寄存器 (A0h) 的 OSDE 位从 “00” 到 “01” 或 “10”，LED 开路/短路寄存器会开始存储开路/短路信息，在过了至少 2 个扫描周期后，MCU 就可以从 B3h~C4h 寄存器中读取到开路/短路信息，在设置配置寄存器的 OSDE 位的时候，开路/短路数据是不会被刷新的。

检测行为是一种一次性的行为，每次在读取开路/短路信息之前，配置寄存器的 OSDE 位需从 0 变为 1。

“ghost” 这个词是用来描述某个 LED 灯处于 OFF 态，但在别的 LED 灯打开时，却有比较淡的发光。鬼影现象通常发生在 LED 多路复用的时候。在阵列结构中，任何在恒流输出端或者 PCB 到 LED 灯的寄生电容都可能提供足够的电流去点亮某个 LED 灯，从而导致鬼影现象。

为了防止这种鬼影，在 HTR3239 中，对于每个 SWx 有多组下拉电阻，对于每个 CSy 有多组上拉电阻，选择合适的下拉和上拉电阻可以有效限制鬼影现象。

芯片关断模式可用于减少功耗。在芯片关断模式下，所有寄存器保持原数据不变。

通过对配置寄存器 (A0h) 中的 SSD 位置 “0”，芯片进入软件关断模式，所有的电流输出端口关闭，所有的寄存器都可以改写。

### Hardware Shutdown

The chip enters hardware shutdown when the SDB pin is pulled low. All analog circuits are disabled during hardware shutdown. The chip releases hardware shutdown when the SDB pin is pulled high. During hardware shutdown state, Function Register can be operated.

If VCC has risk drop below 1.75V but above 0.1V during SDB pulled low, please re-initialize all Function Registers before SDB pulled high.

当 SDB 脚拉低时, 芯片进入硬件关断模式。所有的模拟电路都被关断。

当 SDB 脚拉高时, 芯片退出硬件关断模式。在硬件关断模式下, 寄存器可以被操作。

如果在 SDB 拉低的时候 VCC 电压掉到了 0.1V 到 1.75V 之间, 那么在 SDB 拉高之前请重新配置寄存器的值。

## 8 Register Map

Table4 Register Map

| Register Address | Name                                     | Function                                                                                   | R/W | Default Value |
|------------------|------------------------------------------|--------------------------------------------------------------------------------------------|-----|---------------|
| 03h~8Fh          | PWM Register                             | Set PWM value for LED<br>设置 PWM 的值                                                         | R/W | 0000 0000     |
| 92h~9Fh          | Scaling Register                         | Control the DC output current of each CSy<br>控制每一路 CS 的直流输出                                | R/W | 0000 0000     |
| A0h              | Configuration Register                   | Configure the operation mode<br>配置运行模式                                                     | R/W | 0001 0000     |
| A1h              | Global Current Control Register          | Set the global current<br>设置全局电流                                                           | R/W | 0000 0000     |
| B0h              | Pull Down/Up Resistor Selection Register | Set the pull down resistor for SWx and pull up resistor for CSy<br>设置 SWx 的下拉电阻和 CSy 的上拉电阻 | R/W | 0011 0011     |
| B1h              | Spread Spectrum Register                 | Spread spectrum function enable<br>扩频功能使能                                                  | R/W | 0000 0000     |
| B2h              | PWM Frequency Register                   | Set the PWM frequency<br>设置 PWM 频率                                                         | R/W | 0000 0001     |
| B3h~C4h          | Open/Short Register                      | Store the open or short information<br>存储开路或者短路的信息                                         | R   | 0000 0000     |
| CFh              | Reset Register                           | Reset all register to POR state<br>重启所有寄存器                                                 | W   | 0000 0000     |

### Register Address: 03h~8Fh, PWM Register (default 0000 0000)

| Bit   | Label | Default  | Description                                                                                                                                                                                                                               |
|-------|-------|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| D7:D0 | PWM   | 00000000 | Each dot has a byte to modulate the PWM duty in 256 steps. The value of the PWM Registers decides the average current of each LED, see the following formula.<br>每个点都有一个字节去控制 256 个台阶的 PWM 占空比, 每个 PWM 寄存器的值决定了每个 LED 电路的平均电流, 具体可参考公式说明。 |




Figure 9 PWM Register Map

The average current of each LED  $I_{LED}$  can be computed by Formula:

$$I_{LED} = \frac{PWM}{256} \times I_{OUT(PEAK)} \times Duty$$

$$PWM = \sum_{n=0}^7 D[n] \times 2^n$$

Where Duty is the duty cycle of SWx, n=9 or 8 .....:

$$Duty = \frac{30\mu s}{30\mu s + 0.8\mu s + 0.27\mu s} \times \frac{1}{n}$$

$I_{OUT}$  is the output current of CSy (y=1~16):

$$I_{OUT(PEAK)} = \frac{342}{R_{ISET}} \times \frac{GCC}{64} \times \frac{SL}{256}$$

GCC is the Global Current Control Register (A1h) value, SL is the Scaling Register value (92h~9Fh) and  $R_{ISET}$  is the external resistor of  $I_{SET}$  pin.

$$SL = \sum_{n=0}^7 D[n] \times 2^n$$

每个 LED 电路的平均电流  $I_{LED}$  计算如下:

$$I_{LED} = \frac{PWM}{256} \times I_{OUT(PEAK)} \times Duty$$

$$PWM = \sum_{n=0}^7 D[n] \times 2^n$$

Duty 是 SW 的占空比时间, 其中 n 表示路数。

$$Duty = \frac{30\mu s}{30\mu s + 0.8\mu s + 0.27\mu s} \times \frac{1}{n}$$

$I_{OUT}$  的输出电流为

$$I_{OUT(PEAK)} = \frac{342}{R_{ISET}} \times \frac{GCC}{64} \times \frac{SL}{256}$$

GCC 是 Global Current Control Register (A1h) SL 是 Scaling Register value (92h~9Fh)  $R_{ISET}$  是  $I_{SET}$  引脚上的外部电阻值

$$SL = \sum_{n=0}^7 D[n] \times 2^n$$

#### Register Address: 92h~9Fh, Scaling Register (default 00000000)

| Bit   | Label | Default  | Description                                                                                                                                                                                                                                                                                                             |
|-------|-------|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| D7:D0 | SL    | 00000000 | Scaling register control the DC output current of each CSy. Each CSy has a byte to modulate the scaling in 256 steps. The value of the Scaling Register decides the peak current of each LED noted $I_{OUT(PEAK)}$ .<br>扫描寄存器控制 CSy 每一路的直流输出电流, 每一个 CSy 都有 1byte 在 256 阶范围内控制扫描信号。扫描寄存器的值决定了每个 LED 的 peak 电流。具体可参考公式说明。 |




Figure 10 Scaling Register Map

**Register Address: A0h, Configuration Register (default 00010000)**

| Bit   | Label | Default | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|-------|-------|---------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| D7:D4 | SWS   | 0001    | SWx Setting<br>0000: SW1~SW9, 9SWx15CS matrix<br>0001: SW1~SW8, 8SWx16CS matrix<br>0010: SW1~SW7, 7SWx16CS matrix, SW8 no-active<br>0011: SW1~SW6, 6SWx16CS matrix, SW7~SW8 no-active<br>0100: SW1~SW5, 5SWx16CS matrix, SW6~SW8 no-active<br>0101: SW1~SW4, 4SWx16CS matrix, SW5~SW8 no-active<br>0110: SW1~SW3, 3SWx16CS matrix, SW4~SW8 no-active<br>0111: SW1~SW2, 2SWx16CS matrix, SW3~SW8 no-active<br>1000: SW1~SW9 with same phase, all on.<br>Others no use |
| D3    | LGC   | 0       | H/L logic 高低逻辑电平<br>0: 1.4V/0.4V<br>1: 2.4V/0.6V                                                                                                                                                                                                                                                                                                                                                                                                                     |
| D2:D1 | OSDE  | 00      | Open Short Detection Enable 开路短路检测使能<br>00: 关闭开路短路检测 Disable open/short detection<br>01/11: 开路检测使能 Enable open detection<br>10: 短路检测使能 Enable short detection                                                                                                                                                                                                                                                                                                        |
| D0    | SSD   | 0       | Software Shutdown Control 软件关闭控制<br>0: 软件关闭 Software shutdown<br>1: 正常工作 Normal operation                                                                                                                                                                                                                                                                                                                                                                            |

**Register Address: A1h, Global Current Control Register (default 00000000)**

| Bit   | Label    | Default | Description                                                                                                                                                                                                                                                                          |
|-------|----------|---------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| D7    | Reserved | 0       |                                                                                                                                                                                                                                                                                      |
| D6:D0 | GCC      | 0000000 | The Global Current Control Register modulates all CSy (y=1~18) DC current which is noted as I <sub>OUT</sub> in 65 steps, maximum GCC is "100 0000", if GCC>"1000000", GCC= "100 0000".<br>全局电流控制寄存器控制 CSy(y=1~18)的直流电流 (65 个台阶), 最大设置值为 1000000, 如果 GCC 大于 1000000, 则 GCC 为 1000000 |

**Register Address: B0h, Pull Down/Up Resistor Selection Register (default 00110011)**

| Bit   | Label    | Default | Description                                                                                                                                                                                                                                                                                        |
|-------|----------|---------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| D7    | PHC      | 0       | Phase choice, 相位选择<br>0: 0 度相位延迟 0 degree phase delay<br>1:180 度相位延迟 180 degree phase delay                                                                                                                                                                                                        |
| D6:D4 | SWPDR    | 011     | SWx Pull down Resistor Selection, SWx 下拉电阻选择寄存器<br>000: No pull-down resistor<br>001: 4.0kΩ only in SWx off time<br>010: 8.0kΩ only in SWx off time<br>011: 0.5kΩ only in SWx off time<br>100: 8.0kΩ all the time<br>101: 0.5kΩ all the time<br>110: 1.0kΩ all the time<br>111: 2.0kΩ all the time |
| D3    | Reserved | 0       |                                                                                                                                                                                                                                                                                                    |
| D2:D0 | CSPUR    | 011     | CSy Pull up Resistor Selection CSy 上拉电阻选择寄存器<br>000: No pull up resistor<br>001: 4.0kΩ only in CSx off time<br>010: 8.0kΩ only in CSx off time<br>011: 0.5kΩ only in CSx off time<br>100: 8.0kΩ all the time<br>101: 0.5kΩ all the time                                                            |

|  |  |  |                                                    |
|--|--|--|----------------------------------------------------|
|  |  |  | 110: 1.0kΩ all the time<br>111: 2.0kΩ all the time |
|--|--|--|----------------------------------------------------|

**Register Address: B1h, Spread Spectrum Register (default 00000000)**

| Bit   | Label    | Default | Description                                                                         |
|-------|----------|---------|-------------------------------------------------------------------------------------|
| D7:D6 | Reserved | 00      |                                                                                     |
| D5    | SSP      | 0       | Spread spectrum function enable 扩频使能<br>0: 禁止 Disable<br>1: 使能 Enable               |
| D3:D2 | RNG      | 00      | Spread spectrum range 扩频范围<br>00 ±5%<br>01 ±15%<br>10 ±24%<br>11 ±34%               |
| D1:D0 | CLT      | 00      | Spread spectrum cycle time 扩频周期选择<br>00 1980μs<br>01 1200μs<br>10 820μs<br>11 660μs |

**Register Address: B2h, PWM Frequency Register (default 00000001)**

| Bit   | Label    | Default | Description                                                                                                                                      |
|-------|----------|---------|--------------------------------------------------------------------------------------------------------------------------------------------------|
| D7:D3 | Reserved | 00000   |                                                                                                                                                  |
| D2:D0 | PWMF     | 001     | PWM frequency setting PWM 频率设置<br>000 55kHz<br>001 32kHz<br>010 4kHz<br>011 2kHz<br>100 1kHz<br>101 0.5kHz(n≤4)<br>110 0.25kHz(n≤2)<br>111 80kHz |

**Register Address: B3h~C4h, Open/Short Register (Read Only)**

| Bit   | Label     | Default      | Description                                                                                                                                                                                                                                                                                                                                                                   |
|-------|-----------|--------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| D7:D0 | CS08:CS06 | 0000000<br>0 | <p>When OSDE (A0h) is set to "01", open detection will be triggered once, and the open information will be stored at B3h~C4h.</p> <p>当 OSDE(A0h) 设置为"01"开路检测会检测一次，开路信息就会存储到 B3h~C4h</p> <p>When OSDE (A0h) set to "10", short detection will be triggered once, and the short information will be stored at B3h~C4h</p> <p>当 OSDE(A0h) 设置为"10"短路检测会检测一次，短路信息就会存储到 B3h~C4h</p> |


| Bit | CSx\SWx | SW1  | SW2  | SW3  | SW4  | SW5  | SW6  | SW7  | SW8  | SW9  |
|-----|---------|------|------|------|------|------|------|------|------|------|
| D7  | CS8     | 0xB4 | 0xB6 | 0xB8 | 0xBA | 0xBC | 0xBE | 0xC0 | 0xC2 | 0xC4 |
| D6  | CS7     |      |      |      |      |      |      |      |      |      |
| D5  | CS6     |      |      |      |      |      |      |      |      |      |
| D4  | --      |      |      |      |      |      |      |      |      |      |
| D3  | --      |      |      |      |      |      |      |      |      |      |
| D2  | --      |      |      |      |      |      |      |      |      |      |
| D1  | --      |      |      |      |      |      |      |      |      |      |
| D0  | --      |      |      |      |      |      |      |      |      |      |
| D7  | --      | 0xB3 | 0xB5 | 0xB7 | 0xB9 | 0xBB | 0xBD | 0xBF | 0xC1 | 0xC3 |
| D6  | CS5     |      |      |      |      |      |      |      |      |      |
| D5  | CS4     |      |      |      |      |      |      |      |      |      |
| D4  | CS3     |      |      |      |      |      |      |      |      |      |
| D3  | CS2     |      |      |      |      |      |      |      |      |      |
| D2  | CS1     |      |      |      |      |      |      |      |      |      |
| D1  | --      |      |      |      |      |      |      |      |      |      |
| D0  | --      |      |      |      |      |      |      |      |      |      |

**Register Address: CFh, Reset Register**

| Bit   | Label | Default      | Description                                                                                                                                                                                                                                                                                                        |
|-------|-------|--------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| D7:D0 | Reset | 0000000<br>0 | <p>Once user writes the Reset Register with any value, HTR3239 will reset all the HTR3239 registers to their default value. On initial power-up, the HTR3239 registers are reset to their default values for a blank display.</p> <p>当用户在 Reset 寄存器中写入任意值，HTR3239 会复位所有的寄存器到他们的初始值。在初始上电的过程中，HTR3239 也会被复位到初始值</p> |



**PACKAGE OUTLINE**

SPN (SOP24)




| Symbol | Dimensions In Millimeters |        | Dimensions In Inches |       |
|--------|---------------------------|--------|----------------------|-------|
|        | Min                       | Max    | Min                  | Max   |
| A      | 2.350                     | 2.650  | 0.093                | 0.104 |
| A1     | 0.100                     | 0.300  | 0.004                | 0.012 |
| A2     | 2.100                     | 2.500  | 0.083                | 0.098 |
| b      | 0.330                     | 0.510  | 0.013                | 0.020 |
| c      | 0.204                     | 0.330  | 0.008                | 0.013 |
| D      | 15.200                    | 15.600 | 0.598                | 0.614 |
| E      | 7.400                     | 7.600  | 0.291                | 0.299 |
| E1     | 10.210                    | 10.610 | 0.402                | 0.418 |
| e      | 1.270 (BSC)               |        | 0.050 (BSC)          |       |
| L      | 0.400                     | 1.270  | 0.016                | 0.050 |
| θ      | 0°                        | 8°     | 0°                   | 8°    |

# TAPE AND REEL INFORMATION




|           |                                                                 |
|-----------|-----------------------------------------------------------------|
| <b>A0</b> | Dimension designed to accommodate the component width; 料槽宽度     |
| <b>B0</b> | Dimension designed to accommodate the component length; 料槽长度    |
| <b>K0</b> | Dimension designed to accommodate the component thickness; 料槽厚度 |
| <b>W</b>  | Overall width of the carrier tape; 载带整体宽度                       |
| <b>P1</b> | Pitch between successive cavity centers; 相邻槽中心间距                |

## 编带 PIN1 方位象限分配 Quadrant Assignments for Pin1 Orientation in Tape



| 器件料号<br>Part No. | 封装类型<br>Package Type | 封装标识<br>Package Code | 引脚数<br>Pins | SPQ | 料盘直径<br>$D_R$ (mm) | 料盘宽度<br>W1 (mm) | A0 (mm) | B0 (mm) | K0 (mm) | P1 (mm) | W (mm) | Pin1 象限<br>Quadrant |
|------------------|----------------------|----------------------|-------------|-----|--------------------|-----------------|---------|---------|---------|---------|--------|---------------------|
| HTR3239SPNR      | SOP                  | SPN                  | 24          | TBD | TBD                | TBD             | TBD     | TBD     | TBD     | TBD     | TBD    | TBD                 |

**TAPE AND REEL BOX INFORMATION**


| 器件料号<br>Part No. | 封装类型<br>Package Type | 封装标识<br>Package Code | 引脚数<br>Pins | SPQ | 长度<br>Length (mm) | 宽度 Width (mm) | 高度 Height (mm) |
|------------------|----------------------|----------------------|-------------|-----|-------------------|---------------|----------------|
| HTR3239SPNR      | SOP                  | SPN                  | 24          | TBD | TBD               | TBD           | TBD            |

**IMPORTANT NOTICE****注意**

Heroic Electronic Technology (Jiaxing) Co., Ltd (HT) reserves the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any products or services. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete.

禾润电子科技（嘉兴）股份有限公司（以下简称HT）保留对产品、服务、文档的任何修改、更正、提高、改善和其他改变，或停止提供任何产品和服务的权利。客户在下单和生产前应确保所得到的信息是最新、最完整的。

HT assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using HT components.

HT对相关应用的说明和协助以及客户产品的板级设计不承担任何责任。

HT products are not authorized for use in safety-critical applications (such as life support devices or systems) where a failure of the HT product would reasonably be expected to affect the safety or effectiveness of that devices or systems.

HT的产品并未授权用于诸如生命维持设备等安全性极高的应用中。

The information included herein is believed to be accurate and reliable. However, HT assumes no responsibility for its use; nor for any infringement of patents or other rights of third parties which may result from its use.

本文中的相关信息是精确和可靠的，但HT并不对其负责，也不对任何可能的专利和第三方权利的侵害负责。

Following are URLs and contacts where you can obtain information or supports on any HT products and application solutions:

下面是可以联系到我公司的相关链接和联系方式：

**禾润电子科技（嘉兴）股份有限公司****Heroic Electronic Technology (Jiaxing) Co., Ltd.**

地址：浙江省嘉兴市凌公塘路3339号JRC大厦A座三层

Add: A 3rd floor, JRC Building, No. 3339, LingGongTang Road, Jiaxing, Zhejiang Province

Sales: 0573-82585539, sales@heroic.com.cn

Support: 0573-82586151, support@heroic.com.cn

Fax: 0573-82585078

Website: www.heroic.com.cn; wap.heroic.com.cn

Wechat MP: HEROIC\_JX

请及时关注禾润官方微信公众号，随时获取最新产品信息和技术资料！

